



$\sqrt{\text{Ra } 1.6}$ (\surd) $\begin{matrix} +0.2 \\ +0.1 \end{matrix}$ $\begin{matrix} -0.1 \\ -0.2 \end{matrix}$

general tolerances ISO 2768-K

angular deflection +/-20 degrees (see note 1)
 linear force: 75N
 torque: 1Nm
 bakeout temperature: 150deg C max.
 pressure range 1E-11mbar to 1000mbar
 fully UHV compatible materials

note 1: if mounted to wobblestick flange

Material: all UHV compatible		nominal	over	1	6	30	100	300	1000
Wobblestick manipulator with high torque magnet		dimension up to		6	30	100	300	1000	2000
WM		tolerance \pm		0.05	0.1	0.3	0.5	0.8	1.2
		Scale	Drawn	Denys Sutter					
		1:2 (2:1)	Date	07.04.2011					
			changed	28.04.15 vG					
Ferrovac GmbH		THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FERROVAC GMBH. ANY REPRODUCTION IN PART OR AS WHOLE WITHOUT OUR PERMISSION IS PROHIBITED.		Rev.		C			
CH-8050 Zurich						WM40HT-XXXX-YYYY			